

Contract Reproduction Reclaimed Slate

Contract Reproduction Reclaimed Slate Range







Reproduction Reclaimed Grey Slate



Reproduction Country Weathered Reclaimed Slate



Reproduction Reclaimed Westmorland Green Slate

TECHNICAL DATA

Size of Slates	See table
Minimum Pitch (100r	mm lap)
Moderate Exposure	20°
Severe Exposure	25°
Maximum Pitch	90°
Typical Laps (mm)	75, 100
Maximum Guage	253 - 266
Covering Capacity (N	let Slates/m²)
75mm Lap	12.28
100mm Lap	13.63
Weight of Slating (Ap	prox, kg/m²)
75mm Lap	30
100mm Lap	35
Battens Required (Ne	et lin.m/m²)
75mm Lap	3.8
100mm Lap	3.95
Batten Size Recomm	ended (fixed to BS 5534)
50 x 25mm for rafter	s/supports not
exceeding 600mm c	entres
Slate Nails	38mm x 3.35 Gauge
Alloy or Copper Nails	s (Copper to BS1202-2)
Tested to	BS EN 492:2012

Main Slates

_	WIDTH (i	inches)			
HEIGHT		12"	12"	18"	
포	13"	√			
			√	√	
_	WIDTH (ı	mm)			
HEIGHT		300	300		
뮈	325	√			
	600		√	√	

It is recommended that batched crates to be combined/mixed on site $% \left\{ 1,2,\ldots ,n\right\} =0$

Loading Out

Scaffold: When loading out on scaffold please ensure the slates are stacked as they

are stacked in the pallet on head of slate and face away.

Roof: Ensure slates are loaded horizontally on battens with slate side face down

For more information on our products

Telephone: 01484 666400 Fax: 01484 662709

E-mail: info@greysartstone.co.uk Website: www.greysroofing.co.uk

Greys Artstone Limited,

Lees Mill, Lees Mill Lane, Linthwaite

Huddersfield HD75QE