

Diminishing Reproduction Slate



New Quarried
Westmorland
Green



Aged
Westmorland
Green



New Quarried
Welsh
Blue/Grey



New Quarried
Welsh
Heather/Purple

Main Slates

HEIGHT	WIDTH	6"	8"	10"	12"	14"	16"	18"	20"
12"		✓	✓	✓					
14"			✓	✓	✓				
16"			✓	✓	✓	✓			
18"				✓	✓	✓	✓		
20"				✓	✓	✓	✓	✓	
22"					✓	✓	✓	✓	✓
24"						✓	✓	✓	✓

Top Slates

HEIGHT	WIDTH	6"	8"	10"
8 1/2"		✓	✓	✓



Under Eaves

HEIGHT	WIDTH	12"
11 1/4"		✓
13 1/4"		✓

Note: Slate sizes marked in red (✓) will be available from October 2018



TECHNICAL DATA

Size of Slates	See table
Minimum Pitch (100mm lap)	27°
Maximum Pitch	90°
Typical Laps (mm)	75
Weight of Slating (Approx, kg/m²) 75mm Lap	38
Battens Required (Net lin.m/m²) 75mm Lap	6.5
Batten Size Recommended (fixed to BS 5534) 50 x 25mm for rafters/supports not exceeding 600mm centres	
Slate Nails	38mm x 3.35 Gauge Alloy or Copper Nails (Copper to BS1202-2)
Tested to	BS EN 492:2012

This product is a "Proprietary Product" it is therefore outside the scope of BS 5534:2014 (Slating and tiling for pitched roofs and vertical cladding). Code of practice and installation should therefore be carried out in accordance with manufacturer's instructions.

For more information on our products

Telephone: 01484 666400

Fax: 01484 662709

E-mail: info@greysartstone.co.uk

Website: www.greysroofing.co.uk

Greys Artstone Limited, Burdwell Works,
New Mill Road, Brockholes, Holmfirth,
Huddersfield HD9 7AZ